

Titan™		End weight		
		15 kg	20 kg	>20 kg
Fattening	Birds per pan	70–80	50–60	40–50
		End weight 3.75 kg		
Rearing	Birds per pan	70–80		
Animal info				
		Females	Males	
Minimum age at removal (weeks)		16	22	
Average weight at removal (kg)		13	20	
Density automatic ventilation (birds/m <sup>2</sup> )		4.4–5.5	1.9–2.4	
Max. daily feed intake (g/bird)		320	550	
Technical info				
Pan	Material	polypropylene		
	Diameter	540 mm		
	Average pan content	1 kg (min.) – 4 kg (max.)		
Transport	Outside diameter tube	50.8 mm / 44.5 mm		
	Drive unit (***) / (****)	0.37 kW – 1/2 HP (***) / 0.55 kW – 3/4 HP (****)		
		3 phase 50 Hz (***) / 3 phase 60 Hz (****)		
		350 rpm (***) / 420 rpm (****)		
	Average transport capacity	450 kg/h		
	Max. length per fill point	200 m (for 50.8 mm tube)		
		150 m (for 44.5 mm tube)		
Suspension	Suspension points	max. every 3 m		
Installation time (including assembly, suspension and electricity supply)		3 skilled people: 1 line (100 m per day)		
<p>(*) in well ventilated (automatic ventilation) houses  (**) in open sided (natural ventilation) houses  (***) based on 50 Hz  (****) based on 60 Hz</p>				